

## AIR-TO-AIR MISSILES



[British AAMs](#)

[Chinese AAMs](#)

[French AAMs](#)

[Israeli AAMs](#)

[Italian AAMs](#)

[Russian AAMs](#)

[South African AAMs](#)

[US AAMs](#)

**Firestreak**

Notes: Firestreak was an early British heat-seeking missile, roughly analogous to the Sidewinder (though much larger). The testing program started in 1954, and the missile was so successful that for the first 100 launches, the engineers learned practically nothing about any potential weaknesses of the Firestreak. (Later testing revealed an accuracy rating of about 85% when fired within the proper parameters, still a remarkable total.) The Firestreak had been largely replaced by later missiles by 2003, though the few countries still using the Lightning (mostly Saudi Arabia and Kuwait) still had some Firestreaks on hand.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Firestreak	137 kg	Average	IR	Rear Aspect	\$7400

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Firestreak	5095	1065	8000	C47 B100	26C	FRAG-HE

**Red Top**

Notes: The Red Top began as an upgrade to the Firestreak (and was originally called the Firestreak Mk IV). The Red Top was to overcome the narrow angle of acquisition of the Firestreak, as well as to rearrange the components of the Firestreak in a more logical and efficient pattern. Increases in technology allowed a better seeker head and the change in design as well as explosives technology allowed a more lethal warhead. However, by 2003, the Red Top has the same status as the Firestreak; largely in storage except for those countries still using the Lightning.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Red Top	150 kg	Average	IR	All Aspect	\$11416

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Red Top	5435	1000	12000	C56 B94	26C	FRAG-HE

**Skyflash**

Notes: The Skyflash is a development of the AIM-7E2 Sparrow. The homing head has been replaced by one using a more advanced monopulse seeker that increases accuracy and allows the warm-up time for the missile to be decreased from the 15 seconds of the standard AIM-7E2 to less than 2 seconds. This decreases the minimum range and response time. The Skyflash was designed for the British variant of the Phantom II; it was also used by the Viggen and the Tornado. By 2003, Skyflash was largely replaced in Europe by the AMRAAM, and was on its way to replacement in other areas of the world.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Skyflash	193 kg	Average	Radar	All Aspect	\$17256

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Skyflash	6795	1600	50000	C54 B106	23C	FRAG-HE

**EODTC PL-2 Pili**

Notes: The PL-2 family is based on the Russian K-13 (NATO Name, AA-2). An entire family of PL-2-series missiles were designed; however, none but the PL-2 and PL-5 entered production. Both were heat-seeking missiles, though radar-homing versions were also designed and failed testing. Today, the PL-2 series is used only by China.

The basic PL-2 is roughly the same in appearance as the AIM-9B Sidewinder; this is not by accident (though the story will be deferred until the K-13 in Russian AAMs). It is also roughly of the same abilities as the AIM-9B. The PL-2, piggybacking on Russian work, entered development in 1964 and production in 1966, though full production did not occur until 1970. Because of the long development time, it had features that the K-13 did not. Later versions of the PL-2 equipped the PLAAF's fighters, and the PL-2B still equips its older fighters and ground attack aircraft. The PL-2B has clipped control surfaces, as this allowed it to be carried to be carried by a greater number of aircraft, in greater numbers, and did not affect the performance envelope of the missile.

The PL-2-J72 and PL-2-519 were limited production versions which were actually put into service. The PL-2-J79 is a light version with greater acceleration, but a smaller engine and less range. It was designed for dogfighting and for shorter-range combat. The PL-2-519 is a version of the PL-2A, with a larger motor to push a larger warhead but a long minimum range and shorter maximum range. These latter two were not produced in anywhere near the numbers that the other PL-2s were produced, but did reach full production.

The PL-3 was supposed to be an improved version of the PL-2 and PL-2A, and was to be the first AAM to be designed and built in China. It was to be an all-around improvement of the PL-2A, but Chinese technology did not prove up to the task, and only 50 PL-3s were built for testing. The PL-3, though promising, simply could not achieve the design goals and was dropped without going into production. The improvements of the PL-3 could largely be built into the PL-2B and the PL-3 was terminated in 1983, in favor of the PL-2B. Progress on the PL-3 was delayed by setbacks during the Cultural Revolution. The PL-3 was originally going to be a quite different missile than the PL-2, but the first batch of 20 missiles was ready in 1968, with the next 50 not ready until 1981. By this time, it had already been replaced by the PL-2B, and the PL-3 was deemed a failure, or at least superfluous. Stats for the PL-3 are included for comparison.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
PL-2	75.3 kg	Difficult	IR	Rear Aspect	\$6580
PL-2A	60 kg	Difficult	IR	Rear Aspect	\$6620
PL-2B	76 kg	Average	IR	Rear Aspect	\$7210
PL-2-72	53 kg	Difficult	IR	Rear Aspect	\$6120
P-2-519	152.8 kg	Difficult	IR	Rear Aspect	\$7252
PL-3	93 kg	Difficult	IR	Rear Aspect	\$6906

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
PL-2	3720	1500	7600	C20 B45	12C	HE
PL-2A	3955	1500	8055	C28 B55	12C	HE
PL-2B	3900	1000	10000	C28 B45	12C	HE
PL-2-72	4325	1000	8000	C20 B39	10C	HE
P-2-519	3680	2700	6000	C23 B46	12C	HE
PL-3	3580	1500	11500	C27 B50	13C	HE

**EODTC PL-5 Pili**

Notes: The PL-2 series was, for the most part, a serviceable family of missiles, but the Chinese wanted better missiles, along the line of the PL-5B, but improved. The PL-5 series is entirely Chinese-made, but follows the Soviet practice of developing radar-homing and heat-seeking versions of the same missile. It is essentially a scaled-up PL-2B, differing in cooling of the seeker, larger engine, and larger warhead. Work began on the SARH version began in 1966; the IR version development began in 1972. However, there were numerous technological and budgetary delays and the first flying examples of either type did not begin until 1972. The first testing batch ran out quickly, and the second, larger batch was not available until 1984, after even more teething pains. Before this batch was built, the radar-homing was dropped, felt to be unnecessary. The production IR version of the PL-5 was delayed even further, and was not available for deployment until 1986. By then, though, the PL-5 was a top-notch weapon.

Though the PL-3 was largely incorporated into the PL-2B, the PLAAF felt that all of the technological improvements could not be put into the PL-2B. They decided to place the PL-3's insides into a PL-5A. The new missile was called the PL-6, and design work began in 1975, actually before the design work on the PL-3 began. However, the design changes could easily be placed into the PL-5B, and except for LRIP, the PL-6 was not produced in large numbers. Stats are provided for general interest and because the PL-6 was issued in small numbers.

The PL5A/B/C/6 are capable of only boresight shots, so it is not that maneuverable. The PL-5C and PL-6 are capable of 21g maneuvers and turn, and cannot be fired off boresight. The PL-5E is capable of 40g maneuvers. Other versions are capable of 18g maneuvers. The PL-5 was designed to compete with the AIM-9L, and the PL-5E exceeds this goal, though earlier versions do not.

The PL-5 has been widely exported.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
PL-5A	150 kg	Difficult	Radar	All Aspect	\$12006
PL-5B	148 kg	Average	IR	Rear Aspect	\$8576

<b>PL-5C</b>	148 kg	Average	IR	Side Aspect	\$14606
<b>PL-5E</b>	83 kg	Average	IR	Side Aspect	\$7490
<b>PL-6</b>	93 kg	Average	IR	Side Aspect	\$10186

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>PL-5A</b>	3350	1300	10000	C63 B80	22C	HE
<b>PL-5B</b>	3350	800	16000	C63 B80	22C	HE
<b>PL-5C</b>	3350	600	21700	C28 B55	22C	HE
<b>PL-5E</b>	3350	600	25100	C54 B106	22C	HE-FRAG
<b>PL-6</b>	3580	1300	11500	C17 B63	13C	HE-FRAG

### Zhouzhou PL-7 Pan Lung

Notes: The PL-7 is acknowledged to be copy of the MDBA Matra Magic 1, but it also considered to be a somewhat of a crude copy, without all the performance specifications of the Magic 1, especially the range. Some of the internal electronics of the PL-7 are in fact the same as the PL-5E. Some even go as far as claiming that the PL-7 is a PL-5E put into a Magic 1 airframe. It does have the ability to slave the IR seeker heads to the carrying aircraft's radar, and the ability to engage in high-g flight to chase targets. Its acceleration, believed to accelerate to full speed in seconds, is a help. It is a lightweight missile with carrying aircraft able to carry more of them than usual.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
<b>PL-7</b>	89 kg	Average	IR	Side Aspect	\$11501

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>PL-7</b>	2145	500	7000	C41 B65	18C	HE

### Luoyang PL-8 Pen Lung

Notes: At first on the QT, China made an agreement to eventually produce the Python-3 in China, and modify it for Chinese aircraft use. (It turned out that the aircraft were made more compatible with the missile instead of vice versa; this made the aircraft eventually more compatible with advanced technology.) PL-8s at first retained their Western electronics suite and dogfight agility, but were also supplemented with Chinese systems. The PL-8 was sort of an interim missile, to be used until all Chinese aircraft had been modified to use the soon-to-be-coming PL-9. Nonetheless, on its own, it was a quite capable missile, despite its limitations. The PL-8 is about equivalent to the AIM-9L in performance and counter-countermeasures. PL-8s were also upgraded so that modern PL-8s are equivalent to the PL-9. The PL-8 is the base Python-3, straight from Israel; the PL-8A is license assembled in China with Israeli parts; and the PL-8B is 100% built in China. The PL-8H is a SAM version and has a 10 kilogram warhead (as opposed to the 11 kilogram warhead of the rest of the PL-8 series; this will be covered elsewhere).

The PL-9 is essentially the perfected form of the PL-8, able to function with Chinese, Russian, and Chinese electronics, and able to be sold to most of the world. The PL-9 is capable to be slaved to the aircraft's radar, AWACS radar, or DASH HMS. There are two air-air variants: the PL-9, the standard variant, and the PL-9C, the short-range high-agility variant. The standard PL-9 can fire 40% off-boresight shots; the PL-9C can fire 60-degree off-boresight shots. The PL-9C has a larger continuous rod warhead. Both have ECCM and IRCCM performance about equal to the AIM-9M Sidewinder, being one level harder to decoy with flares or countermeasures. The DK-9, also known as the PL-9D, is a SAM version of the PL-9, able to interface with AWACS or Western, Russian, or Chinese air defense networks. (This will be covered in the SAM sections). On some aircraft, the PL-9 is capable of interfacing with a helmet-sight.

Export versions, the PL-9D have only a 9000-meter range, and do not have the ECCM and IRCCM resistance that the PL-9B has.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
<b>PL-8</b>	115 kg	Average	IR	All Aspect	\$15000
<b>PL-9</b>	115 kg	Average	IR	All Aspect	\$16666
<b>PL-9C</b>	115 kg	Easy	IR	All Aspect	\$18333

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>PL-8</b>	3216	500	14000	C31 B81	18C	HE-FRAG
<b>PL-9</b>	3752	500	15000	C31 B81	18C	HE-FRAG
<b>PL-9C</b>	2144	300	22000	C32 B84	19C	HE-FRAG

### Luoyang PL-10 Pili

Notes: Also known as the High Agility Close Combat Missile, the PL-10 has been seen in two distinct airframes: one looks like the German IRIS-T, the other looks like the South African A-Darter. The A-Darter-based airframe appears to be the actual version, with the IRIS-T airframe being a testing model. The PL-10 is capable of extreme agility; some sources put g tolerance at as much as 45g, with 90-degree off-boresight shots and using over-the-shoulder launches. It is a short-range missile, carrying a high-impulse

engine and a warhead of the continuous rod type/cube fragmentary type. Though primary guidance is by heat-seeking, the missile also has a laser fusing module. The PL-10 may be used with helmet-sight interface (if the firing aircraft is so equipped). Though the PL-10 has ECCM and IRCCM capabilities like those of the PL-9, physical performance is close to the abilities of the AIM-9X Sidewinder.

The Chinese have also deployed a SAM version, the LY-10. This will be covered (eventually under the SAM section).

Weapon	Weight	Accuracy	Guidance	Sensing	Price
PL-10	89 kg	Easy	IR	All Aspect	\$17058

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
PL-10	4287	300	22000	C41 B94	18C	HE-FRAG

### SAST PL-11 Pili

Notes: The PL-11 is part of a family of weapons which includes a SAM system and an antiradiation missile. The PL-11 may be seen as an improved Aspide AAM; it is a huge missile, 286 millimeters in diameter, 3.99 meters long, with a nearly 40-kilogram continuous rod warhead. It follows the same planform as the Aspide, Though electronics have been improved to match the latest Chinese avionics capabilities, the airframe is obviously based on the Aspide (which is itself based on the AIM-7E2 Sparrow). The basic PL-11 missile is capable of lock-on before firing shots or lock-on after firing shots; accuracy degraded by one place when using a lock-on after firing shot.

The PL-12 was made in three varieties: The original PL-11, which is an Aspide with a few alterations. The PL-11A can be launched conventionally, or using inertial guidance; the pilot, if he keeps track of the missile only then must he lock on. (This sort of lock on is one level more difficult.) The PL-11B is an active radar homing version. It should be noted that the active homing of the missile does not take over until the missile has traveled 2475 meters; until, a lock on must be maintained. However, the PL-11B is capable of tracking 12 targets at once; if it misses its original target, and there are more targets in range and within its target cone (60 degrees wide), it can switch to targeting another target.

Despite its effectiveness, the PL-11 was a limited production missile which is no longer in production. It was seen as a stopgap for use until the even more advanced PL-12 was ready.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
PL-11	310 kg	Average	Radar	All Aspect	\$17255
PL-11A	310 kg	Average	Radar*	All Aspect	\$67267
PL-11B	310 kg	Average	Active Radar	All Aspect	\$27461

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
PL-11	3215	915	75000	C123 B163	36C	HE-FRAG
PL-11A	3215	915	75000	C123 B163	36C	HE-FRAG
PL-11B	3215	915	75000	C123 B163	36C	HE-FRAG

### CATIC PL-12 Pili

Notes: Though development of the PL-12 started in the late 1990s, the Chinese ran into technological troubles until the Chinese made development of the BVR active-homing PL-12 a priority in 2002. The PL-12 is sometimes called the AMR-1 for Active, Missile, Radar. It is also called by Western pilots by the name of "SinoAMRAAM." It does, in fact highly-resemble the AIM-120A or B, though the details of the rear fins are different. It is likely that the AHM package and avionics are similar to those of the R-77. (This is much expected -- The Chinese bought a small lot of R-77s from the Russians in the late 1990s.) The motor, however, has much more burn time than either the R-77's or AIM-120's and much longer range than either. It also is believed to use thrust vectoring. It is a much smaller missile than the PL-11, and can be carried on the wingtip pylons of some Chinese fighters.

The PL-12 may be used in four ways: SARH (one level more accurate, but requires the aircraft to lock-on and keep it); the PL-12 may be launched using inertial navigation out to a certain range, then it turns on its own active seeker (one level more difficult); it can be fired like a conventional active homing missile, with the missile's seeker taking over after traveling halfway to the target; or it can use Home On Jam, with a difficult chance to guide itself using its active seeker towards an enemy ECM emitter. The PL-12 has a maneuvering limit of 48gs, making it slightly more effective than the AIM-120A and B, but less than the AIM-120C.

There are five versions of the PL-12: The basic PL-12; the PL-12A, with an improved motor; the PL-12B, with upgraded avionics; the PL-12C, with folding fins, and the PL-12D, which has a belly intake and a rocket boost motor along with a ramjet sustainer motor, making it one of the longest-ranged AAMs in the world at present. (The booster takes the PL-12D up to Speed 447, requiring one phase, and then the ramjet kicks in to take it up to full speed.)

The PL-12 also has two export models: the SD-10 and SD-10A. The SD-10 is similar to the PL-12, but has solid rear fins instead of lattice fins, and no thrust vectoring. It has a g-limit of only 38. The SD-10A was designed to be compatible with Western aircraft and avionics, but is otherwise the same as the SD-10.

In addition, a SAM version and an ARM version exist, which will be dealt with in the appropriate sections.

Weapon	Weight	Accuracy	Guidance	Sensing	Price

<b>PL-12</b>	180 kg	Average	Active Radar	All Aspect	\$26146
<b>PL-12A</b>	195 kg	Average	Active Radar	All Aspect	\$26590
<b>PL-12B/C</b>	195 kg	Easy	Active Radar	All Aspect	\$29249
<b>PL-12D</b>	205 kg	Easy	Active Radar	All Aspect	\$37349

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>PL-12</b>	4300	305	70000	C62 B113	23C	HE-FRAG
<b>PL-12A</b>	4300	305	100000	C62 B113	23C	HE-FRAG
<b>PL-12B/C</b>	4300	305	100000	C62 B113	23C	HE-FRAG
<b>PL-12D</b>	4400	305	230330	C62 B113	23C	HE-FRAG

**LETRI PL-13 Pan Lung**

Notes: Though an original development, the PL-13 uses a great deal of design work and technology gleaned from other missiles. The overall body appears to be similar to the French MICA, with the engine extension allowing it to do medium-range interceptions. The body also has a slightly coke-bottle (area-ruled) cross-section, and is equipped with strakes through about half its body like the Russian R-77 (AA-12 Adder), and the reverse-trapezoidal rear fins are similar to those in the front of the R-27 (AA-10 Alamo). It is rumored that the PL-13 uses some thrust vectoring, but details are lacking. The PL-13 is very maneuverable and is capable of instantaneous high-g turns. The PL-13 is believed to have folding fins, as it was designed to be able to fight the F-22 Raptor. Like virtually all radar-homing missiles, it can be guided by another properly-equipped aircraft; in addition, the PL-13 can be guided and/or get a lock-on by any Chinese AWACS-type aircraft. Maneuverability-wise, performance is said to be on par with the AIM-9X Sidewinder, even though the PL-13 is an active radar-homing missile. Shots up to 60 degrees off boresight are possible, though over-the-shoulder shots are not possible with the PL-13. Lock On After Launch shots are possible (and something Chinese fighter pilots heavily train on). The PL-13 is also one of the fastest AAMs in existence with quick acceleration, though range is subpar due to its limited fuel and the high-rate of fuel consumption to achieve its high velocity. The PL-13 was designed, however for short to medium-range engagements, and specifically to dogfight the F-22 Raptor, and is not meant for BVR combat.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
<b>PL-13</b>	185 kg	Easy	Active Radar	All Aspect	\$23092

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>PL-13</b>	5360	300	20800	C44 B94	19C	HE-FRAG

**LETRI PL-14 Pan Lung**

Notes This missile is the result of a technology transfer between South Africa and China, producing an almost exact copy of their Meteor long-range AAM. Note that the Meteor program was canceled in South Africa due to funding; though the South Africa were primarily in selling the technology of the Meteor to other countries, they also may be interested in buying a perfected Meteor. Its primary feature is a two-intake ramjet engine that gives the PL-14 great range, and it is designed for long-range BVR combat. Chinese AWACS-type aircraft can provide target information to the launching aircraft, and guide the PL-14 until the active radar takes over. The primary method of attack for the pilot using a PL-14 is to launch without lock on on inertial guidance, achieving a quick lock-on and terminal active radar guidance. A standard active radar profile, where the missile must travel one-quarter of the distance to the target before the active radar of the missile kicks in. The PL-14 uses a long, slim body with trapezoidal rear fins and no fore-fins or strakes, and thus probably uses thrust vectoring. The PL-14 is probably the longest-ranged AAM in the world at present. The PL-14 has strong ECCM capability, and decoying and jamming effects are one level more than normal.

The Meteor is now being developed by a consortium of European countries, MBDA. The PL-14 has numerous differences., however, particularly in range and electronics.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
<b>PL-14</b>	185 kg	Easy	Active Radar	All Aspect	\$47529

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>PL-14</b>	4395	300	250000	C44 B94	19C	HE-FRAG

**607 Institute PL-15 Pili**

Notes: The PL-15 was designed to be a smaller, lighter PL-12; the PL-12 in a J-20 Stealth Fighter's weapon bay is an extremely tight fit. However, it does appear that the PL-15 is supplanting the PL-12. Diameter (and consequently warhead) are reduced, as is the length, and the fins are clipped. The motor is a two-stage rocket, instead of the ramjet of some earlier models. The PL-15 therefore has outstanding range without it likely uses thrust vectoring. The electronics are similar to a PL-14's and PL-12's with similar firing modes. However, if the ECM environment is too much for the PL-15, it can switch to IR Guidance, and in either mode, the PL-15 may change targets as necessary if it misses its original target. The PL-15 may be ripple-fired, at the same or different (of the aircraft is capable of this).

Weapon	Weight	Accuracy	Guidance	Sensing	Price
PL-15	162 kg	Easy	Active Radar	All Aspect	\$65422

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
PL-15	4400	300	300000	C39 B88	17C	HE-FRAG

### CATIC PL-21 Pan Lung

Notes: The PL-21 is a smaller version of the PL-21D, with a somewhat smaller warhead and shorter engine with a larger boost rocket and smaller fuel tank for the ramjet. The result is, a missile with a shorter range (making it a medium-range BVR), but an advanced enhanced-blast/fragmentation warhead that is so accurate it often kills by impact with the target.(and then the warhead goes off), though it does have a proximity fuse. It, like the PL-12D, has a ramjet motor, though with only one intake and a shorter ramjet engine. The PL-21's motor burns until it hits its target or reaches maximum range, giving full speed until detonation; and accelerating to full speed within 1 second.. Guidance is similar to other Chinese Active Homing missiles, however it is designed for heavy ECM environments and decoying or using ECM is two levels more difficult.

A deficit of the PL-21 is that the ramjet plume is so large that the PL-21 can actually be tracked, and possibly intercepted, by enemy heat-seeking missiles. The PL-21 is a long missile, some 6 meters long, barely fitting into the J-20 stealth fighter's weapons bay. The fins fold for easier carriage. Unlike most active homing missiles, the PL-21 must only fly one-quarter the range to the target before the missile radar takes over. It can also use the engagement parameters of the PL-12D.

The PL-21 is also known as the "Charlie 21" by Western pilots, and the A2A (which simply means air-to-air ).

The PL-21 also has a dumbed -down export version, which differs primarily in its electronics suite. ECM is one level more difficult to affect it, and only a modicum of ECCM (no more than normal ECM).

Weapon	Weight	Accuracy	Guidance	Sensing	Price
PL-21	200 kg	Easy	Active Radar	All Aspect	\$36756

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
PL-21	4400	300	160000	C98 B90	23C	HE-FRAG

**Magic R.550**

Notes: This is France's standard heat-seeking missile, and is also used by several countries around the world that do business with France such as Algeria, Belgium, and several Middle East countries. It can also be used by helicopters.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Magic I	89 kg	Average	IR	Side Aspect	\$7295
Magic II	89 kg	Easy	IR	All Angle	\$9370

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Magic I	3775	600	12800	C29 B75	17C	FRAG-HE
Magic II	3775	400	24000	C34 B80	17C	FRAG-HE

**Mica**

Notes: This is the French counterpart to the AMRAAM, used by France and by countries that conduct frequent arms trade with France, such as Iraq. It is an active homing missile with its own radar unit in the nose to allow it to home in on targets without help from the firing aircraft. The missile is one level harder to decoy with various ECM devices and chaff. There is also an IR homing version of this missile.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Mica RH	110 kg	Easy	Active Radar	All Aspect	\$24830
Mica IR	110 kg	Easy	IR	All Aspect	\$9400

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Mica	5200	1200	50000	C49 B100	20C	FRAG-HE
	5200	300	32000	C49 B100	20C	FRAG-HE

**Super 530**

Notes: This French missile comes in two types, a standard radar homing missile and the active homing Super 530D. It is used by many French-built aircraft and other French customers. It is a very fast missile, and is a very heavy missile. It was being replaced by Mica as the century began.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Super 530	275 kg	Average	Radar	All Aspect	\$23,680
Super 530D	275 kg	Average	Active Radar	All Aspect	\$25,685

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Super 530	5425	2000	37000	C76 B125	32C	FRAG-HE
Super 530D	5425	2000	37000	C101 B144	32C	FRAG-HE

**Derby**

Notes: Also known as Alto, this is an active homing missile based on the Python. Derby was in development for more than a decade before the first one was possibly fielded in 1998 (this is not confirmed by the IAF). The Derby combines the light weight of the Python with advanced guidance. Though not confirmed, rumors say the Derby has been offered to India, China, South Korea, and the Philippines.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Derby	120 kg	Easy	Active Radar	All Aspect	\$45856

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Derby	5945	1100	50000	C48 B100	17C	FRAG-HE

**Python-3**

Notes: This AAM was the successor to the Shafrir 2 of the late 1970s. The basic form is similar to the Safrir and the Sidewinder, but it has a new seeker head with a wider angle view than most heat-seeking missiles. The fins are large for more agility. It is a fast, yet lightweight missile capable of quick maneuvers to follow its target.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Python-3	120 kg	Average	IR	All Aspect	\$9736

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Python-3	5945	600	15000	C34 B70	17C	FRAG-HE

**Python-4**

Notes: This is an advanced Israeli air-to-air heat-seeking missile. It is well known to Arab pilots as a maneuverable and deadly missile with high resistance to IRCM and decoys (one level more resistant to countermeasures. It may be used in conjunction with a helmet-mounted sight used by some Israeli aircraft. It is an all-angle missile. Its proximity fuze is one of the best in the world.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Python-4	120 kg	Easy	IR	All Aspect	\$9736

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Python-4	5945	500	15000	C38 B88	17C	FRAG-HE

**Shafrir-2**

Notes: Beginning with the AIM-9B Sidewinder as a basis, Israeli designers at Rafael sought to produce a more lethal and accurate missile. The first thing they did was to dramatically increase the diameter of the missile, from 127mm to 160mm. The mechanisms were simplified, and solid-state electronics were used instead of vacuum tubes. The Shafrir-1 did not enter service, but an improved model, the Shafrir-2, did, and it is credited with the destruction of over 200 aircraft in the 1973 Yom Kippur war alone.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Shafrir-2	93 kg	Average	IR	Rear Aspect	\$5296

## Israeli Air-to-Air Missiles

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>Shafrir-2</b>	3100	600	6400	C29 B75	17C	FRAG-HE

**Aspide**

Notes: This missile is externally almost identical to the US Sparrow missile – with good reason. The Aspide was intended to cut into the European market for AIM-7E Sparrow missiles, and whatever other markets it could get into. Internally, the Aspide is very different from the Sparrow. The radar head is improved, with significant ECCM capability, to the point where all decoying attempts against the Aspide are one level harder. It is capable of a look-down, shoot-down intercept. The rocket motor is likewise improved, with the Aspide being capable of Mach 4 speeds. The Italians and the Spanish still use the Aspide, but most European sales went to the new AMRAAM instead.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
Aspide	220 kg	Average	Radar	All Aspect	\$23724

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
Aspide	6795	3200	75000	C54 B106	23C	FRAG-HE

**AA-1 Alkali**

Notes: This was the first Russian air-to-air missile, and is debatable whether it was the first or second AAM to go into service in the world. It was a rather clumsy arrangement; the early form of the missile is a beam-riding missile, with the missile homing on a coded radar beam instead of a standard radar lock-on. The pilot must keep the missile and target in a rather narrow radar beam, and course corrections are transmitted directly to the missile by a radio link. There were at least 6 variants of the Alkali, most can be identified by differing fin shapes; they also had different homing heads and warheads. The last AA-1 was retired from Russian service by 1977, and most other countries soon thereafter, but they can occasionally be encountered under the wings of Third World Aircraft.

Twilight 2000 Notes: In perhaps one of the most unexplainable engagements of the Twilight War, an Albanian MiG-17 managed to down a US F/A-22A Raptor using an AA-1E Alkali.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AA-1A	91 kg	Formidable	Beam Riding	Rear Aspect	\$2248
AA-1B	91 kg	Formidable	Radar	All Aspect	\$6232
AA-1C	91 kg	Formidable	IR	Rear Aspect	\$4232
AA-1D	83.2 kg	Difficult	Radar	All Aspect	\$6200
AA-1E	83.2 kg	Difficult	IR	Rear Aspect	\$4448
AA-1F	83.2 kg	Difficult	Radar	All Aspect	\$6320

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AA-1A	1700	2000	6000	C27 B75	22C	FRAG-HE
AA-1B	1700	1600	6800	C34 B80	22C	FRAG-HE
AA-1C	1700	1100	6800	C34 B80	22C	FRAG-HE
AA-1D	1700	1600	8000	C41 B94	22C	FRAG-HE
AA-1E	1700	1100	8000	C44 B94	22C	FRAG-HE
AA-1F	1700	1600	8000	C47 B100	22C	FRAG-HE

**AA-2 Atoll**

Notes: On 24 September 1958, an AIM-9B Sidewinder missile lodged in the tail of a Chinese MiG-17 without exploding. This missile was taken to the then-Soviet Union and, based on this missile, the Russian's first successful air-to-air missile was developed, the AA-2 Atoll. The missile was also developed into an early radar-homing weapon for all angle attacks.

Twilight 2000 Notes: The Atoll was still in common use in Warsaw Pact countries, Third World nations, and China (where it is known as the PL-1) during the Twilight War.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AA-2	70 kg	Difficult	IR	Rear Aspect	\$3,010
AA-2-2	70 kg	Difficult	Radar	All Aspect	\$22,395

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AA-2	3960	1000	6500	C14 B50	11C	FRAG-HE
AA-2-2	3960	1200	8000	C14 B50	11C	FRAG-HE

**AA-3 Anab**

Notes: The AA-3 is an early Russian radar homing missile designed with a large warhead to shoot down bombers. It is not a particularly accurate missile and it is vulnerable to countermeasures, but its explosions usually destroy an aircraft. It is produced by China as the PL-2.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AA-3A	275 kg	Difficult	Radar	All Aspect	\$23,505
AA-3B	275 kg	Difficult	IR	Rear Aspect	\$12,930

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AA-3A	4750	1200	19000	C98 B100	35C	HE
AA-3B	4750	1200	19000	C98 B100	35C	HE

**AA-6 Acrid**

Notes: This huge air-to-air missile was originally designed to be used by MiG-25 Foxbat to shoot down the US B-70 Valkyrie bomber. (It was killed by Congress instead.) The Acrid is so big because of the long-range rocket motor, the large radar kit, and because of the limitations of Soviet technology in the early 1960s when the AA-6 was designed. Early AA-6 missiles didn't have look-down capability, but the "C" model rectified this. The "B" model is an IR version of the Acrid, but the range is much more limited, again due to the technology of the time. MiG-25s are still sometimes seen with Acrids, but they have mostly been replaced with later technology.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AA-6A	800 kg	Difficult	Radar	All Aspect	\$13352
AA-6B	748 kg	Difficult	IR	Rear Aspect	\$10308
AA-6C	748 kg	Average	Radar	All Aspect	\$11952

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AA-6A	6795	3200	50000	C150 B175	53C	FRAG-HE
AA-6B	6795	3200	15500	C150 B175	53C	FRAG-HE
AA-6C	6795	2145	50000	C180 B194	53C	FRAG-HE

### AA-7 Apex

Notes: This is one of the standard air-to-air missiles on Russian aircraft, used primarily by the MiG-23, MiG-27, and its variants. There are four variants: The AA-7A basic radar homing missile, the AA-7B heat-seeker, and the AA-7C and AA-7D with extended range.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AA-7A	320 kg	Difficult	Radar	All Aspect	\$23,740
AA-7B	320 kg	Difficult	IR	Rear Aspect	\$13,280
AA-7C	320 kg	Average	Radar	All Aspect	\$23,750
AA-7D	320 kg	Average	IR	Rear Aspect	\$13,280

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AA-7 R-23R	4750	1500	35000	C73 B85	26C	HE
AA-7 R-23T	4750	800	15000	C73 B85	26C	HE
AA-7 R-24R	4750	1500	50000	C85 B90	26C	HE
AA-7 R-24T	4750	800	21000	C85 B90	26C	HE

### AA-8 Aphid

Notes: This former standard Pact heat-seeking missile was still in widespread use in the Twilight War, both by the Pact forces and by Third-World countries. It is a wide-aspect missile, able to guide from the side or rear of the target aircraft.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AA-8A	65 kg	Average	IR	Side Aspect	\$13,010
AA-8B	65 kg	Average	IR	All Aspect	\$15,010
AA-8C	65 kg	Average	IR	All Aspect	\$15,010

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AA-8A	2600	800	10000	C19 B62	13C	FRAG-HE
AA-8B	2600	800	13600	C23 B68	13C	FRAG-HE
AA-8C	2600	400	13600	C26 B75	13C	FRAG-HE

### AA-9 Amos

Notes: This missile was designed to arm MiG-31 interceptors, but was later used on MiG-25s. It was designed to be state-of-the-art (at the time, 1980), used to attack bombers and attack aircraft using low-level penetration techniques, cruise missiles, helicopters, and high-speed aircraft like the SR-71 (a task at which it was never successful). It was also the Soviet Union's first active homing missile, able to guide itself once it closes to 48 kilometers using its own radar.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AA-9	490 kg	Average	Active Radar	All Aspect	\$61008

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AA-9	7645	4800	160000	C190 B200	50C	FRAG-HE

### AA-10 Alamo

Notes: This missile was designed to form the main part of the MiG-29s air-to-air armament. It is a modular missile allowing for upgrades as well as different seeker heads and warheads to be placed on the same basic missile airframe. There are five variants of the Alamo, two heat-seeking, two radar-homing, and one active homing missile. The AA-10 is a high-agility missile able to be used in close in dogfights as well as long-range intercepts.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AA-10A	254 kg	Average	IR	All Aspect	\$10460
AA-10B	253 kg	Average	Radar	All Aspect	\$8660

<b>AA-10C</b>	350 kg	Average	Radar	All Aspect	\$9136
<b>AA-10D</b>	343 kg	Easy	IR	All Aspect	\$19000
<b>AA-10E</b>	349 kg	Easy	Active Radar	All Aspect	\$49136

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>AA-10A</b>	6795	1070	80000	C70 B118	28C	FRAG-HE
<b>AA-10B</b>	6795	1600	70000	C70 B118	28C	FRAG-HE
<b>AA-10C</b>	6795	1600	130000	C70 B120	28C	FRAG-HE
<b>AA-10D</b>	6795	1050	120000	C80 B130	28C	FRAG-HE
<b>AA-10E</b>	6795	1600	130000	C80 B130	28C	FRAG-HE

**AA-11 Archer**

Notes: This is the standard heat-seeking missile of Russian forces and allies. The missile is resistant to jamming (one level harder to decoy) and is very maneuverable. Three versions are available, the standard AA-11A, the longer range AA-11B, and the still longer range AA-11C. It is an all-angle missile, able to engage from any angle, instead of just the rear of the target.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
<b>AA-11A</b>	96 kg	Average	IR	All Aspect	\$15270
<b>AA-11B</b>	105 kg	Average	IR	All Aspect	\$15320
<b>AA-11C</b>	115 kg	Easy	IR	All Aspect	\$15385

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>AA-11A</b>	3665	600	20000	C38 B88	19C	FRAG-HE
<b>AA-11B</b>	3665	600	30000	C44 B94	19C	FRAG-HE
<b>AA-11C</b>	3665	600	40000	C44 B94	19C	FRAG-HE

**AA-12 Adder**

Notes: This weapon is colloquially known as the AMRAAMski, so similar it is to the AIM-120 AMRAAM missile. It is known for its maneuverability. It is an active radar missile, guiding itself by means of a radar seeker in its head.

Twilight 2000 Notes: This missile was greatly feared by Western pilots during the Twilight War. Luckily, this weapon was not put into production until just prior to the Twilight War and the factories were put out of operation early, so the AMRAAMski was rarely encountered.

Merc 2000 Notes: Budget cuts meant that the AMRAAMski was always in short supply.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
<b>AA-12</b>	175 kg	Easy	Active Radar	All Aspect	\$25,400

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>AA-12</b>	6500	1500	100000	C60 B112	23C	FRAG-HE

**R-Darter**

Notes: Unlike the other Darter AAMs, the R-Darter (Radar Darter) is a development of the Israeli Derby AAM. The R-Darter uses an active radar seeker head and is highly resistant to countermeasures (one level harder to decoy). It also has home-on-jam ability, something the Derby does not have; the R-Darter can actually home in on a source of jamming signals on a 1D10 roll of 7+ if it has closed to within 20 km of its target and it loses its lock-on due to ECM activity.

Twilight 2000 Notes: This weapon is in extremely short supply; perhaps less than 30 were available at the start of Twilight War hostilities, and very few were produced after that point.

Merc 2000 Notes: R-Darter development slowed to a trickle then stopped altogether in 2002. The South Africans bought Derby missiles from Israel instead.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
R-Darter	118 kg	Easy	Active Radar	All Aspect	\$50296

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
R-Darter	6000	1000	50000	C48 B100	17C	FRAG-HE

**U-Darter**

Notes: The U-Darter (Upgraded Darter) was developed specifically for use by the SAAF for use by their Cheetah aircraft. It can be used by other aircraft and some helicopters, however. The biggest differences are a greater weight and size with an increased lethality warhead and improved guidance features.

Twilight 2000 Notes: Though limited quantities of the U-Darter were available for the Twilight War, most SAAF aircraft were still using the V-3C Darter and earlier missiles.

Merc 2000 Notes: This missile rivaled the Sidewinder and AA-8 for the title of "most-exported air-to-air missile."

Weapon	Weight	Accuracy	Guidance	Sensing	Price
U-Darter	96 kg	Easy	IR	All Aspect	\$9728

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
U-Darter	3500	200	10000	C48 B100	17C	FRAG-HE

**V-3 Kukri/Darter**

Notes: This weapon entered production in 1981 to arm South African Mirages, Impalas, (and later) Cheetahs. It is similar in form to the French R.550 Magic, and is probably simply a domestically-produced version of the Magic with a few improvements and tweaks. The V-3A is the original missile, virtually identical to the Magic; the V-3B is a bit larger, heavier, and more capable; and the V-3C is even larger and heavier.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
V-3A Kukri-A	73 kg	Average	IR	Side Aspect	\$7264
V-3B Kukri-B	75 kg	Average	IR	All Aspect	\$9264
V-3C Darter	89 kg	Average	IR	All Aspect	\$9484

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
V-3A Kukri-A	3700	300	8000	C21 B68	12C	FRAG-HE
V-3B Kukri-B	4245	300	8000	C21 B70	12C	FRAG-HE
V-3C Darter	3400	200	6200	C37 B88	17C	FRAG-HE

### Hughes AIM-4/AIM-26 Falcon

Notes: The Falcon was the first operational air-to-air missile. Though not particularly reliable or accurate in its early iterations, it did provide a valuable technological base for later developments. Development began in late 1946 as a short-range subsonic missile to give bombers a self-defense capability, but quickly changed to a supersonic fighter-launched missile with the designation XAAM-A-2. In 1950, the Falcon became operational, and in 1951, the designation was changed to F-98, and then changed again to GAR-1 in 1955. AIM-4Ds were initially used by F-4D Phantoms in Vietnam, but quickly withdrawn because the visual ROEs imposed in Vietnam made the long minimum range of the Falcon problematic. The missile accelerates quickly, but is none too maneuverable; this limits its effectiveness somewhat. By the early 1970s, the Falcon had largely been replaced by missiles with later technology. The Swedes used a version of the AIM-26B (as the RB-27) for almost two decades after the Falcon had been withdrawn from service elsewhere.

The original GAR-1 (later AIM-4) used radar-homing guidance with a relatively short range. The GAR-1 also has no proximity fuze, meaning that the GAR-1 actually had to strike its target before the 3.4-kilogram warhead would detonate. As the GAR-1 was to be used against large, subsonic bombers, this was not considered a problem at the time. The GAR-1D (later AIM-4A) offered greater maneuverability due to enlarged control surfaces, including separate auxiliary control surfaces at the rear of the primary fins. An improved motor also made it a bit faster than the GAR-1. The GAR-2 (AIM-4B) used the same airframe, but was a heat-seeking missile. The GAR-2A (AIM-4C) had an improved IR seeker. The GAR-2B (AIM-4D) further improved the IR seeker.

The GAR-3 (AIM-4E) was a bit larger, with an improved motor and larger warhead, and with the GAR-3, the name of the missile was changed to Super Falcon. The GAR-3A (AIM-4F) improved the rocket motor further by providing a boost and sustainer motor, as well as improving (slightly) ECM resistance; earlier radar-homing versions were upgraded to this standard. The GAR-4 (AIM-4G) was the heat-seeking variant of the GAR-3A, and also had an improved IR seeker.

The GAR-11 (AIM-26A; officially the Falcon, but often called the Nuclear Falcon) was a very different type of air-to-air missile. It was designed to destroy formations of bombers at once, using a small nuclear warhead. The GAR-11 was developed in 1959, when the radar seeker used in the Falcon was still deemed too inaccurate to ensure bomber destruction; hence the nuclear warhead. The GAR-11 used a radar proximity fuze, but the range was rather short since the GAR-11's warhead was much heavier than the standard Falcon. This meant that the Nuclear Falcon could conceivably put the firing aircraft within range of the EMP, radiation, or even damage or destruction radius of the warhead; the pilot had a shield he could erect over the front of his canopy to prevent flash blinding, but this did not do anything to protect him from anything else.

The GAR-11A (AIM-26B) Super Falcon was developed as a conventional counterpart to the GAR-11, at the same time as the GAR-11. It was much larger and heavier than any of the AIM-4 series, and was radar-homing and triggered by a proximity fuze. The GAR-11A, however, lacked look-down-shoot-down capability, and was primarily used by the Swedes in an improved version.

Twilight 2000 Notes: Increasing numbers of Falcons and Super Falcons were pulled out of storage, particularly in Europe; they were also adapted to a much wider variety of aircraft than they were originally meant for.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AIM-4 Falcon	50 kg	Formidable	Radar	All Aspect	\$15256
AIM-4A Falcon	54 kg	Formidable	Radar	All Aspect	\$15300
AIM-4B Falcon	59 kg	Formidable	IR	Rear Aspect	\$5232
AIM-4C Falcon	61 kg	Difficult	IR	Rear Aspect	\$5394
AIM-4D Falcon	61 kg	Difficult	IR	Side Aspect	\$7360
AIM-4E Super Falcon	68 kg	Difficult	Radar	All Aspect	\$15440
AIM-4F Super Falcon	68 kg	Average	Radar	All Aspect	\$15712
AIM-4G Super Falcon	66 kg	Average	IR	Side Aspect	\$7398
AIM-26A Nuclear Falcon	92 kg	Average	Radar	All Aspect	\$1.5 Million
AIM-26B Super Falcon	119 kg	Average	Radar	All Aspect	\$17040

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AIM-4 Falcon	4750	2145	8000	C25 B75	17C	FRAG-HE
AIM-4A Falcon	5095	2145	9700	C25 B75	17C	FRAG-HE
AIM-4B Falcon	5095	1050	9700	C25 B75	17C	FRAG-HE
AIM-4C Falcon	5095	1050	9700	C25 B75	17C	FRAG-HE
AIM-4D Falcon	6800	1030	9700	C30 B80	17C	FRAG-HE
AIM-4E Super Falcon	6800	2100	11300	C30 B80	17C	FRAG-HE
AIM-4F Super Falcon	6800	2100	11300	C30 B80	17C	FRAG-HE
AIM-4G Super Falcon	6800	1000	11300	C30 B80	17C	FRAG-HE
AIM-26A Nuclear Falcon	3400	3220	8000	Special	Special	0.25 Kiloton
AIM-26B Super Falcon	3400	3220	9700	C40 B106	17C	FRAG-HE

### Raytheon AIM-7 Sparrow

Notes: Research on what eventually became the AIM-7 began in 1947, when the US Navy asked Sperry to develop a beam-riding version for the standard (at the time) 5-inch HVAR rocket. The 5-inch diameter of the rocket proved to be too small, so it was enlarged to 8 inches. The development proved to be full of problems, so much that the first aerial intercept against a drone did not occur until

1952, and the AAM-N-2 Sparrow I (later called the AIM-7A) did not see fleet service until 1956.

The AIM-7A proved to be a failure. Beam-riding guidance is inaccurate for an aircraft-launched missile, and the AIM-7A was easily confused by ground clutter. In addition, the AIM-7A launch system required that the aircraft's radar be slaved to an optical sight, turning a missile which had decent range (at the time) into a VFR weapon. The AIM-7A was withdrawn after only 3 years, with only 2000 being built.

The AAM-N-3 Sparrow II (later called the AIM-7B) was an early attempt at an active-homing missile, developed by Douglas Aviation. Unfortunately this idea was essentially decades ahead of its time in 1955, and the result was a failure. The US Navy, who originally asked for the Sparrow II to arm its F5D-1 Skylancer, canceled its participation in the Sparrow II program in 1956. The Canadians then thought the AIM-7B was the perfect armament for the CF-105 Arrow interceptor, and when the CF-105 project died The Sparrow II died its final death. The AIM-7B is not included in the charts below. A version of this missile, the AIM-7B Sparrow IIX, was also designed; this was to be armed with the same nuclear warhead as on the MD-2 Genie version of the AIM-4 Falcon, but it too was cancelled along with the CF-105 project.

The Sparrow III series began in 1955 with the AAM-N-6 (later called the AIM-7C). It was also at this point that Raytheon became the prime contractor for the AIM-7. Perhaps the key change in guidance was that the Sparrow III series homed in on a radar lock-on from the firing aircraft. This can make a missile highly vulnerable to even simple countermeasures, and this was especially true of early-model Sparrow IIIs (countermeasures are one level more effective against the AIM-7C, 7D, and 7E series).

The AIM-7C used a 29.5 kg continuous-rod fragmentation warhead and a solid-rocket motor. Again, only about 2000 were built, due to the imminent introduction of the AAM-N-6a (AIM-7D). The missile body was essentially the same, but internally, the AIM-7D was quite different. The AIM-7D used liquid propellant that was inert until ignition, which increased the range and ceiling. The seeker was improved to allow for higher closing rates of speed (as occurred with head-on shots), and the first ECCM/anti-jamming capability was introduced. The USAF also used the AIM-7D, calling it the AIM-101 at the time and making it the primary armament of the F-4C Phantom II. After the AIM-7E was introduced, many surviving AIM-7Ds were converted to training missiles with inert warheads, and designated ATM-7D.

In 1963, due to the Pentagon's switch to a common nomenclature system, the earlier versions of the Sparrow were redesignated AIM-7. The next version of the Sparrow III series was the AIM-7E. Propellant was changed back to solid fuel, and the engine again increased range. The AIM-7E was also a bit more agile than its predecessors. The AIM-7E was employed extensively in Vietnam, where opinions of its effectiveness depended on the pilot – most pilots reviled the AIM-7E due to numerous failures of the engine to fire, the seeker losing track of the aircraft's lock-on, the fuzes not working, poor maneuverability, and confusion by ground clutter. On the other hand, some pilots, like the ace Steve Ritchie, swore by the AIM-7E, using it for all five of his MiG kills. Most pilots in Vietnam learned quickly to fire the AIM-7E (and AIM-7s in general) in pairs to decrease the chance of failures. These shortcomings led to the introduction of the AIM-7E2 in 1969, with much improved maneuverability, a shorter minimum range, and improved fusing reliability. The AIM-7E3 further improved the reliability of the fusing and also improved the motor start system, and the AIM-7E4 was designed for use with aircraft with higher-power radars (such as the F-14, introduced in 1973). Otherwise, for game purposes, the AIM-7E3 and E4 are identical to the AIM-7E2. The AIM-7J is an AIM-7E2 license-built in Japan. The RIM-7E is an AIM-7E adapted for use as a ship-launched SAM; the RIM-7H is the AIM-7E2 adapted for the same role. The primary modification for these missiles are snap-open fins, allowing them to be loaded into box launchers. The various versions of the AIM-7E were the most produced, with almost 30,000 being built.

1972 brought the AIM-7F. The AIM-7F had a greatly-increased range due to a dual-thrust motor that provided a quick boost followed by a sustainer. The guidance and control sections were completely solid-state. This guidance package was also smaller, allowing the use of a 39 kg warhead. With the advent of the AIM-7F, the name of the missile was changed from "Sparrow III" to simply "Sparrow." The AIM-7G was a version of the AIM-7F designed specifically for use with the F-111D, but did not proceed beyond the prototype stage. A RIM-7F version was also built. With the AIM-7F, General Dynamics also began building the Sparrow.

The designations AIM-7H, AIM-7I, AIM-7K and AIM-7L were either skipped or were unsuccessful research models. The AIM-7M designation was chosen for the next iteration of the Sparrow, due to its use of the new monopulse seeker head that allows better performance at low altitude and in high-ECM environments, as well as bringing true look-down-shoot-down capability. The AIM-7M includes a digital computer with re-programmable EEPROM modules. The AIM-7M can operate in a semi-independent manner; once the missile is launched, it uses an autopilot to fly in one of several pre-programmed trajectories, and a lock-on is required only for launch, mid-course update, and terminal guidance. The warhead has also been replaced by blast-fragmentation warhead, rather than pure fragmentation. A RIM-7M version was also produced. The AIM-7N was a prototype improved AIM-7M, but subsequent improvements overtook the program and it was never put into full production.

The AIM-7P appeared in 1987, with an improved guidance module, a computer that uplinks to the pilot for more accurate mid-course and terminal guidance, and an improved look-down/shoot-down capability. ECCM has improved so significantly that countermeasure success is degraded by one level. A RIM-7P version was also built. The AIM-9P is still in production, primarily for the US Navy in its RIM-7P version and for foreign countries that are unable to afford the AIM-120. In addition, Raytheon also upgrades earlier versions of the AIM-7 to the AIM-7P standard for those foreign customers as well as the US military.

The AIM-7Q was essentially a testbed for a new guidance system which used an active-homing head combined with an IR seeker for backup. If the AIM-7Q lost radar contact with the target due to ECM or standard methods of breaking lock-ons, the IR seeker would take over and guide the missile to the target. Conversely, the AIM-7Q could be launched as a heat-seeking missile, using brief pulses of radar to confirm the target. AIM-7Q development apparently ended with no production missiles being fielded.

The final version of the Sparrow was the AIM-7R. The AIM-7R used an AIM-7P-type radar guidance module, but it was paired with

an IR seeker used to improve terminal guidance, similar to the AIM-7Q. The onboard computing power was also considerably increased. Range was increased by enlarging the tail surfaces and making them the only control surfaces, allowing for more fuel to be carried. In game terms, countermeasure success is degraded by one level, and if the missile loses lock-on and is within 3 km of its target, a roll is immediately made to regain contact. Though the AIM-7R was set for production, that production was never carried out, due to high development costs and the impending adoption of the AIM-120 AMRAAM missile. The AIM-7R was cancelled in 1996, but as I often do, I included it anyway just for the heck of it.

**Twilight 2000 Notes:** Sparrows were called into increasing use in the Twilight War as supplies of AMRAAM missiles began to be used up. Most Sparrows used by the United States and NATO in the Twilight War were AIM-7Ps and AIM-7Ms, though some countries were using Sparrows as old as the AIM-7E.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AIM-7A	141 kg	Difficult	Beam Riding	Rear Aspect	\$16724
AIM-7C	172 kg	Difficult	Radar	All Aspect	\$17416
AIM-7D	200 kg	Difficult	Radar	All Aspect	\$17588
AIM-7E	205 kg	Difficult	Radar	All Aspect	\$17760
AIM-7E2	205 kg	Average	Radar	All Aspect	\$17760
AIM-7F	228 kg	Average	Radar	All Aspect	\$17728
AIM-7M	228 kg	Average	Radar	All Aspect	\$17768
AIM-7P	225 kg	Easy	Radar	All Aspect	\$17768
AIM-7R	230 kg	Easy	Radar/IR	All Aspect	\$19036

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AIM-7A	1775	2150	8000	C39 B88	23C	FRAG-HE
AIM-7C	2220	2150	40000	C39 B88	23C	FRAG-HE
AIM-7D	3110	2150	40000	C42 B94	23C	FRAG-HE
AIM-7E	3110	1600	44000	C42 B94	23C	FRAG-HE
AIM-7E2	3110	1070	44000	C47 B100	23C	FRAG-HE
AIM-7F	3550	1600	80000	C54 B106	23C	FRAG-HE
AIM-7M	4500	1600	88000	C60 B112	23C	FRAG-HE
AIM-7P	4500	1200	88000	C75 B125	23C	FRAG-HE
AIM-7R	4500	1200	96000	C75 B125	23C	FRAG-HE

### Raytheon AIM-9 Sidewinder

**Notes:** This was the first AAM to be placed into service, and is perhaps the most plentiful AAM in existence. The designers of the Sidewinder, a small team operating on a shoestring budget when development began at China Lake in 1950, created the first Sidewinder out of almost nothing; the project was drastically underfunded and the designers put a considerable amount of their personal funds into it. They then developed a working homing head and got the design to be taken seriously by the Navy. And the rest is history.

The AAM-N-7 Sidewinder I (later designated the AIM-9A Sidewinder) began low rate initial production for the US Navy in 1955. Only 240 were built, as they were considered field test weapons. The AIM-9A had a small 4.5-kilogram blast-fragmentation warhead with an IR seeker which was not cooled like later models would be. The small warhead was a bit of a problem, since the small size meant it had a kill radius of only 9 meters. The primitive seeker also meant that the AIM-9A could detect targets within a mere 4-degree field of view, and the firing aircraft must be in the "slot" position – directly behind the target. To make matters worse, the AIM-9A, though it could turn at 12G, was limited primarily to non-maneuvering targets due to the extremely narrow field of view, and fusing could be unreliable. The AIM-9B's seeker had a greatly-improved field of view, but was otherwise the same as the AIM-9A. The AIM-9B became the first air-to-air missile to score a kill in September of 1958, when Taiwanese F-86Fs fired them at a gaggle of Chinese MiG-15s – to a great success. Production of the AIM-9B stopped in 1962, with 80,000 being built. The AIM-9F was the European version of the AIM-9B. The primary difference is a more sensitive CO2-based cooler for the seeker head. Also called the AIM-9B FGW.2, the AIM-9F was built in Germany by BGT.

The AIM-9C was a response to the problems with the AIM-9B, with the US Navy trying another tack with the sidewinder – semi-active radar-homing guidance. The AIM-9C was also thought to be a way for aircraft that could not use the AIM-7 Sparrow, such as the F-8 Crusader, to be able to use radar-homing missiles (and in fact, the Crusader was the only aircraft to actually carry the AIM-9C in service). The AIM-9C, however, was perhaps less reliable than the AIM-9B, and only 1000 were built. Most surviving AIM-9Cs were later rebuilt into AGM-122A Sidearm anti-radar missiles.

The AIM-9D was developed in tandem with the AIM-9C, but used a new IR seeker. This seeker had an even narrower field of vision to reduce interference from environmental background radiation like the Sun, clouds, the ground, etc., and it's more aerodynamic shape allowed for faster speed. The AIM-9D also features a much larger 11.34-kilogram continuous rod warhead providing the fragmentation effect warhead. It was built from 1965-69. The AIM-9G was developed for the US Navy, built from 1970-72. An improved AIM-9D, the AIM-9G improved target acquisition probability by not only allowing the seeker head to use preprogrammed search patterns, but by allowing the seeker head to be slaved to the aircraft's radar for target acquisition purposes.

(This is called the SEAM upgrade, for Sidewinder Expanded Acquisition Mode.)

The AIM-9E was the first version of the Sidewinder designed specifically for the US Air Force, though the USAF had already been using earlier versions of the Sidewinder. The AIM-9E was an AIM-9B with an improved seeker with a higher tracking rate and Peltier cooling for the seeker. The AIM-9E2 was a version of the basic AIM-9E with a reduced-smoke motor. The nose of the AIM-9E is longer, and has a conical tip.

The AIM-9H started out as merely an improved AIM-9F for the US Navy, but quickly the improvements added up. The AIM-9H featured solid-state electronics that were more stable and allowed for increased accuracy. The seeker's tracking rate was greatly increased, as the AIM-9H was more agile than any of its predecessors due to its electronic "brain" and the electronic actuators for the fins. Some 7700 were built between 1972 and 1974; though they arrived late in the Vietnam War, the AIM-9H's kill rate was a great improvement over earlier models. The US Navy planned an upgrade for the AIM-9H that would be designated the AIM-9K, but the Navy and Air Force decided to get on the same sheet of music and develop the AIM-9L instead.

The AIM-9J was an improved AIM-9E. The AIM-9J used partial solid-state electronics, an improved motor with a longer burn time, more powerful fin actuators that increased agility, and larger, double-delta canards that further increased agility. It did not, however, quite match the capabilities of the AIM-9H, though it was much less expensive. Most AIM-9Js were made by upgrading AIM-9Bs and AIM-9Es, but new production versions were also built, and designated AIM-9J3. The AIM-9N was at first designated the AIM-9J1, and is an incremental upgrade of the AIM-9J with an improved seeker module (decoying the AIM-9N with flares, natural phenomena, or IRCM is done at a -2 penalty). The rocket motor was also improved for a longer burn time, and the warhead was also somewhat improved. AIM-9Ns were all new production missiles, and many were exported instead of being used by US forces.

The AIM-9L, the first joint-service Sidewinder, was a huge improvement over its predecessors, and based on the AIM-9H. Service began in 1974. It was the first heat-seeking missile that could attack its target from any direction – in addition to homing in on engine exhaust, it could home on the heat of the engines themselves and heat caused by friction on the leading edges of an aircraft. The AIM-9L essentially looked at the heat generated by the entire target rather than by just the tailpipes. The AIM-9L used large-span double-delta canards, solid state electronics, and electrical control actuators, all of which increased accuracy and agility. The seeker used argon-cooled Indium Antimonide, and the fuze was a proximity fuze enhanced by a short-range laser (the AOTD fuze, or Active Optical Target Detector), a much more reliable fuze than on earlier Sidewinders. Warhead weight was about double that of the AIM-9J, but it used more modern explosives and a blast-fragmentation warhead with an annular fragmentation pattern. The AIM-9L was first used in combat by Royal Navy Harriers during the Falklands War, and over 16,000 were built by two companies in the US as well as by Germany and Japan. The AIM-9M is a further development of the AIM-9L, replacing it in production. The AIM-9M has a reduced-smoke motor, an improved guidance module, resistance to countermeasures (decoying the AIM-9M with flares, natural phenomena, and IRCM units is one level more difficult), and generally improved reliability. The blast pattern of the warhead is also somewhat improved, though the warhead is almost identical to that of the AIM-9L. All known Sidewinder kills during Desert Storm were with AIM-9Ms. The AIM-9M began service in 1982. The AIM-9S is an export version of the AIM-9M, with the main difference being that the improved countermeasure resistance is removed.

Originally designed specifically for export, the AIM-9P has found itself in use by the US Air Force in recent years. The AIM-9P is a simpler, less expensive Sidewinder, without many of the advanced electronics and seeker features of the AIM-9L and AIM-9M. There are several flavors of the AIM-9P, depending upon the needs of the receiving country and what the US is willing to let them have; they are all based on the AIM-9B/E/J series, and many are in fact rebuilds. The AIM-9P1 has a laser proximity fuze for increased reliability; the AIM-9P2 adds a reduced-smoke motor to that. The AIM-9P3 adds a more advanced warhead, improved guidance electronics, and faster-actuating control surfaces. The AIM-9P4 replaces the seeker with one based on (but not quite as advanced as) the AIM-9L/M. The AIM-9P5 adds IRCM resistance similar to that of the AIM-9M.

The AIM-9X is the newest Sidewinder, combining the best features of earlier Sidewinders, technology of several advanced experimental versions of the Sidewinder, and a host of new ideas. Development began in 1991, operational deployment began in 2003, and full-rate production began in 2004. The AIM-9X was at first developed by Hughes, but since Raytheon now owns Hughes, the AIM-9X is a Raytheon product. The AIM-9X has the rocket motor and the warhead of the AIM-9M, inside a new airframe; the greatly decreased drag gives the AIM-9X increased speed and range. The fins of the AIM-9X are much smaller than any other Sidewinder; they are there primarily for stability, with steering of the AIM-9X being done by jet vanes (much like thrust vectoring) at the exhaust. The small fins of the AIM-9X allow it to fit inside the weapon bays of the F/A-22 and F-35, but still fit on any standard weapon rail able to take a Sidewinder. The AIM-9X can also interface with the new helmet-mounted sights being fielded on some US and NATO aircraft (the JHMCS). The AIM-9X uses an imaging focal plane array seeker that has a 90-degree off-boresight capability; along with its jet-vane steering, this gives the AIM-9X phenomenal accuracy and agility. The AIM-9X has lock-after-launch capability; the pilot of an aircraft equipped with the AIM-9X and the JHMCS can launch the missile before he has a tone (has acquired the target), then steer the AIM-9X into a position where the missile can acquire the target. It also incorporates an advanced version of SEAM. The resistance to countermeasures is so great that the AIM-9X is two difficulty levels less likely to be thrown off by natural phenomena, flares, or IRCM systems.

In the Vietnam War and the Middle Eastern Wars, some American and Israeli pilots discovered that some ground vehicles (particularly older trucks) gave off a tone strong enough for Sidewinders to home in on them.

Twilight 2000 Notes: The AIM-9X is not available in the Twilight 2000 timeline. The AIM-9S is rare.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AIM-9B	69.2 kg	Difficult	IR	Rear Aspect	\$2844
AIM-9C	84 kg	Difficult	Radar	All Aspect	\$5540

<b>AIM-9D</b>	88.5 kg	Average	IR	Rear Aspect	\$3045
<b>AIM-9E/E2</b>	74.5 kg	Average	IR	Rear Aspect	\$2685
<b>AIM-9F</b>	71.9 kg	Average	IR	Rear Aspect	\$2685
<b>AIM-9G</b>	86.6 kg	Average	IR	Side Aspect	\$8077
<b>AIM-9H</b>	84.5 kg	Average	IR	Side Aspect	\$10076
<b>AIM-9J</b>	78 kg	Average	IR	Rear Aspect	\$3483
<b>AIM-9L</b>	85.3 kg	Average	IR	All Aspect	\$8028
<b>AIM-9M</b>	85.5 kg	Easy	IR	All Aspect	\$16032
<b>AIM-9N</b>	78 kg	Average	IR	Rear Aspect	\$3804
<b>AIM-9P1/P2</b>	78 kg	Average	IR	Rear Aspect	\$3579
<b>AIM-9P3</b>	78 kg	Average	IR	Side Aspect	\$5543
<b>AIM-9P4</b>	78 kg	Average	IR	All Aspect	\$7543
<b>AIM-9P5</b>	78 kg	Average	IR	All Aspect	\$15547
<b>AIM-9S</b>	85.5 kg	Average	IR	All Aspect	\$8831
<b>AIM-9X</b>	85.28 kg	Easy	IR	All Aspect	\$21134

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
<b>AIM-9B/E/E2/F</b>	1775	1600	4200	C7 B28	12C	FRAG-HE
<b>AIM-9C</b>	3550	2100	17700	C18 B62	12C	FRAG-HE
<b>AIM-9D</b>	3550	1600	17700	C18 B62	12C	FRAG-HE
<b>AIM-9G</b>	3550	1500	17700	C18 B62	12C	FRAG-HE
<b>AIM-9H</b>	3550	1500	17700	C18 B62	12C	FRAG-HE
<b>AIM-9J</b>	2665	600	14500	C7 B28	12C	FRAG-HE
<b>AIM-9L</b>	4000	600	22400	C21 B68	12C	FRAG-HE
<b>AIM-9M/S</b>	4200	600	22400	C24 B72	13C	FRAG-HE
<b>AIM-9N</b>	3550	600	19200	C10 B32	12C	FRAG-HE
<b>AIM-9P1/P2</b>	3550	600	21200	C10 B32	12C	FRAG-HE
<b>AIM-9P3/P4/P5</b>	3550	600	21200	C12 B38	13C	FRAG-HE
<b>AIM-9X</b>	5300	300	40000	C24 B72	13C	FRAG-HE

### Raytheon AIM-54 Phoenix

Notes: The Phoenix is a sophisticated, costly, and large missile intended for long-range defense of US Navy vessels, and it had a somewhat tortuous history. Development of what became the Phoenix actually began in late 1960, after the US Navy's long-range F6D Missileer interceptor and its AAM-N-10 Eagle BVR missile was cancelled due to large cost overruns. Hughes Aerospace, then the developer of the missile, then turned to more off-the-shelf technology – an upgrade of the AIM-47 Falcon missile and its associated fire control system, both of which had been previously developed for use by the abortive USAF YF-12A interceptor version of the SR-71 Blackbird. The upgraded missile and fire control system was to arm the US Navy's projected F-111B. Tests of the AIM-54A began in 1965, but by 1967, the F-111B was itself cancelled. However, by 1968, development of the F-14 Tomcat began, and the fire control system and the Phoenix were incorporated into the Tomcat. Squadron service of the AIM-54A finally began in 1974, almost 15 years after its conception.

In form, the AIM-54A resembles a huge version of the AIM-4 Falcon, but it is a far different beast. The Phoenix has a small radar set in its nose, allowing it to home in on a target with minimal guidance updates from the Tomcat once it has closed to within 72 kilometers. Once the Phoenix has closed to within 18.2 kilometers of its target, the Phoenix no longer needs targeting updates from the Tomcat and it guides itself. (If fired from inside of 18.2 kilometers, the Phoenix immediately goes to active homing mode.) The Phoenix has a limited look-down, shoot-down capability (rough terrain can screw up target acquisition), a huge 60 kilogram blast-fragmentation warhead, and a very long range, due to its intended role of destroying Soviet maritime bombers. The Phoenix has three fuzing systems – radar proximity, IR proximity, and impact – to further reduce a miss due to bad fuzing.

The AIM-54B appeared in US Navy inventories in 1977 – but only for a very short time. What exactly the AIM-54B variant was is uncertain, but it was most likely version to test less expensive manufacturing methods, such as sheet steel for the fins. The AIM-54B was never in official US Navy use, and it is likely that the cost-cutting measures were incorporated into production AIM-54As and the newer AIM-54C.

The AIM-54C began development in 1977, with squadron service starting in 1982. The AIM-64C used primarily digital instead of analog components, and look-down-shoot-down capability was improved to increase reliability over rough land terrain and make it more capable against small cruise missiles and antishipping missiles. Perhaps the most important improvement was its ECCM system – The AIM-54C is one level harder to decoy than the AIM-54A. The motor was improved, giving the Phoenix increased range and speed.

Several versions of the AIM-54C were put into service as time went by, each having incremental improvements. One of these was an upgraded warhead, with a 20% greater effectiveness. Another set of improvements was aimed at reliability, improving resistance to both the weather at sea and temperature changes as the Tomcat climbs and dives. These versions are often called the AIM-54C+.

Later, ECCM capabilities were further improved (making them, in game terms, two levels more difficult to decoy), and the computer aboard the Phoenix was given EEPROM memory and better signal processor software, as well as EMP hardening. This version is referred to as the AIM-54C ECCM/Sealed.

By 2004, the Phoenix was officially retired from fleet service, due to its cost and the fact that the Soviet maritime bomber threat has all but disappeared. The Tomcat itself was retired in 2007, and with it, the only US aircraft capable of using the Phoenix. Rumors say that the Iranians still have a dozen or so operational AIM-54As for its F-14s.

**Twilight 2000 Notes:** In the Twilight 2000 timeline, the Phoenix managed to bring down most of the Russian maritime bomber fleet within weeks of the start of hostilities, but stocks dwindled very fast, and could never be replenished as quickly as desired. By 2000, 99% of the available stocks had been expended, and facilities for its production had been destroyed.

**Merc 2000 Notes:** This missile was all but dropped from production by 2000 in favor of the less capable but far less costly AMRAAM.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AIM-54A	453 kg	Average	Active Radar	All Aspect	\$48632
AIM-54C	462 kg	Easy	Active Radar	All Aspect	\$54639
AIM-54C+	464 kg	Easy	Active/Radar	All Aspect	\$56321
AIM-54C (ECCM/Sealed)	464 kg	Easy	Active Radar	All Aspect	\$59137

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AIM-54A	6665	3700	134270	C163 B182	25C	FRAG-HE
AIM-54C	7750	3200	148160	C163 B182	25C	FRAG-HE
AIM-54C+	7750	3200	148160	C190 B200	25C	FRAG-HE
AIM-54C (ECCM/Sealed)	7750	2135	148160	C190 B200	25C	FRAG-HE

### Raytheon AIM-120 AMRAAM

Notes: The AMRAAM (Advanced Medium-Range Air-to-Air Missile) replaced the AIM-7 Sparrow in the inventories of the US and most of its allies in the late 1980s. The project was begun by Hughes Aviation in the late 1970s, and selected in preference to a Raytheon missile; it has since been bought out by Raytheon. Low-rate initial production began in October of 1988, after a lengthy and trouble-fraught testing period that started in 1981. Full-rate production did not begin until 1991, though after that point, stocks of the AIM-7 Sparrow were replaced by the AMRAAM as quickly as possible on US and NATO aircraft. Sales to other countries followed later in the 1990s. Though AIM-120s were carried by aircraft in Desert Storm, none were fired at enemy aircraft; first kill for the AMRAAM, of a MiG-25, occurred in December of 1992 during Operation Southern Watch, the US patrolling the no-fly zone over Iraq.

The AMRAAM is an advanced, active-homing radar-guided missile with its own radar unit in the nose to allow it to be guided without help from the firing aircraft or ground unit once its own radar has acquired a fix on the target. This also helps it to resist countermeasures, the missile can actually home in on a source of radar jamming (Accuracy becomes difficult in this case); this is called home-on jam capability. Decoying this missile with various radar countermeasures is two levels harder than normal. The missile, as stated, does require an initial fix from a ground unit or aircraft radar; the missile begins self-guidance after traveling 2 kilometers (2000 meters). The ground unit or aircraft that gives the AMRAAM the initial radar lock-on does not have to be the same as the firing unit or aircraft, as long as a data link exists between the unit or aircraft locking on and the unit or aircraft firing the AMRAAM.

The initial version, the AIM-120A, is still in use by the US and NATO as well as other countries, though many US and NATO aircraft carry later iterations of the AMRAAM. The AMRAAM is capable of being carried on pylons otherwise used only by the AIM-9 Sidewinder, including wingtip launchers such as those on the F-16 and F/A-18. The AIM-120B, first delivered in 1994, uses an improved guidance system, though inside a standard AIM-120A body. The AIM-120C, first delivered in 1996, has as its primary difference clipped fins; the AIM-120C was designed specifically for carriage inside the F-22 Raptor's weapon bays, though it can and is used by other aircraft. The guidance unit is further upgraded (though not measurable in *Twilight 2000 v2.2* terms). The AIM-120C-4, delivered in 1999, uses an improved warhead. The AIM-120C-5, delivered in 2000, is equipped with a larger, more powerful motor, more miniaturized electronics, and an ECCM upgrade (decoying this version is three levels more difficult than normal). The AIM-120C-5's warhead is also smaller, though it throws a larger fragmentation pattern. It was quickly followed by the AIM-120C-6, which has an improved Target Detection Device (TDD); it only has to travel 1500 meters before its own radar takes over and no longer needs ground or aircraft guidance. The AIM-120C-7 began delivery in 2006; this has increased range, improved ECCM, and an improved seeker (not measurable in *Twilight 2000 v2.2* terms). (This version was requested by the US Navy, who was looking for a partial replacement for the long range they lost with the AIM-54 Phoenix.)

The AIM-120D is in the works; it has a two-way data link so that the firing unit or aircraft can make course corrections if needed (such as if the target maneuvers out of the missiles seeker angle or loses lock due to countermeasures). In addition to radar-homing, the AIM-120D has the assistance of GPS in tracking its target (though GPS is not nearly as effective against a fast-maneuvering target, let alone a moving target; it does give the missile a roll of 10 on a d20 to immediately regain a lost lock-on). The AIM-120D can be fired from High-angle Off BoreSight (HOBS capability); the seeker head has a 120-degree field of "vision." Range is greatly increased; the rocket engine has been enlarged due to further miniaturization and increased in power due to increases in technology. First delivery was expected for 2007, but the program has slipped quite a bit, and fielding has only just begun.

In March of 2021 (exact date unknown), an F-15C fired a test version of the AIM-120D to an unprecedented distance to kill a violently-maneuvering BQM-167 subscale drone, capable of maneuvering at up to 9 Gs, and controlled from the ground with an option

for autonomous flight. This happened at the Eglin-Gulf Test and Evaluation Range. Exact Details have not been released, but I think I can parse out enough details to stat something here. The modified AIM-120 has been cited by a number of sources (each of which has a different theoretical range) of having hit the drone at anywhere from 160-240 kilometers (some say that the test AIM-120's range approaches that of the AIM-54 Phoenix), and the F-15C had a new radar set installed to allow lock-on and radar detection at this range. The fact that the F-15C needed upgraded radar would tend to indicate that the test AIM-120 could fly to the outside of those possible ranges. The test missile did not actually have a warhead; most missiles fired at drones for practice don't actually have a warhead; instead, the drone registers that it has been hit by how close the missile passed, and if the pass is inside its kill radius, and if the missile registered that it was close enough to detonate the "warhead." I would assume that an actual service version of the test AIM-120 could carry a standard AIM-120D warhead. Just to confuse the issue for adversarial countries, the test missile was fired during a WSEP event, in which there were several aircraft firing at drones. The test AIM-120 is said to be heavier than a standard AIM-120D, and the electronics are further miniaturized to reduce weight and make even more room for propellant. The propellant itself has been cited in some sources as being "denser" than that of an AIM-120D. However, the stats below come down mojo and fudge, are highly theoretical, and highly subject to change. The designation I'm using (AIM-120D-5) is not the actual designation (it's supposedly called something like the "AIM-120 Test and Evaluation Missile").

The AMRAAM is also in advanced testing for use as a SAM. This is known as the SLAMRAAM (Surface-Launched AMRAAM) or sometimes the HUMRAAM (HMMWV-launched AMRAAM) by the US Army and is also being tested by the US Marines. This system uses a quintuple missile launcher on the back of a HMMWV, and uses a small acquisition radar on a separate vehicle or ground tripod. Most of this development has been done with the AIM-120A, though other AMRAAMs can be used; no major modifications to the AMRAAM are necessary. SLAMRAAM was to be fielded starting in 2008, but the project deadline has slipped considerably. The SLAMRAAM has received a designation of RIM-120 in some sources, though this designation is not considered official.

Before this, as early as 1995, a joint US/Norwegian project called CLAWS (Complementary Low-Altitude Weapon System) was tested, launching AMRAAMs from modified HAWK SAM launchers (eight AMRAAMs per launcher), but CLAWS was cancelled in 2006.

The NCADE is a test project which has still to bear fruit; it is an anti-ballistic missile version of the SLAMRAAM. The seeker head is replaced with that of the AIM-9X, with two-way data link capability to enable ground or shipboard units to make course changes if necessary. A second stage is added to the basic AMRAAM to increase range and acceleration. It is intended as a shorter-range solution than missiles such as the Patriot. So far, no project date completion plans have been announced and details are lacking, and it will not be covered further here.

Note that in Dale Brown's book series, the AIM-120C is called the Scorpion. This is not an official designation for the AIM-120C. Any ground-launched systems listed above will be stattd in the appropriate section. It should be noted that the AMRAAM is slated to be replaced by the AIM-260 JATM, possibly by 2026 to *begin* to replace the AIM-120.

**Twilight 2000 Notes:** In the Twilight 2000 timeline, the AIM-120A and AIM-120B were the primary radar-homing AAMs for the US, NATO, Saudi Arabia, South Korea, and Japan at the start of the war. (They were more and more replaced by AIM-7 Sparrows as stocks of the AIM-120 ran short.) The AIM-120C is a rare version of the AMRAAM, and the AIM-120C-4 was only just entering service at the start of the Twilight War; only the US had them, and perhaps less than 50 were available. No other iterations of the AIM-120 were available in the Twilight 2000 timeline.

Weapon	Weight	Accuracy	Guidance	Sensing	Price
AIM-120A	157 kg	Average	Active Radar	All Aspect	\$58496
AIM-120B/C	157 kg	Easy	Active Radar	All Aspect	\$59081
AIM-120C-4	157 kg	Easy	Active Radar	All Aspect	\$59377
AIM-120C-5	157 kg	Easy	Active Radar	All Aspect	\$58336
AIM-120C-6	157 kg	Easy	Active Radar	All Aspect	\$58920
AIM-120C-7	157 kg	Easy	Active Radar	All Aspect	\$60229
AIM-120D	157 kg	Easy	Active Radar	All Aspect	\$65873
AIM-120D-5	163 kg	Easy	Active Radar	All Aspect	\$79672

Weapon	Speed	Min Rng	Max Rng	Damage	Pen	Type
AIM-120A/B/C	6700	1000	55000	C59 B114	20C	FRAG-HE
AIM-120C-4	6700	1000	55000	C62 B115	20C	FRAG-HE
AIM-120C-5	7400	1000	70000	C47 B126	20C	FRAG-HE
AIM-120C-6	7400	800	70000	C47 B126	20C	FRAG-HE
AIM-120C-7	7400	800	88000	C47 B126	20C	FRAG-HE
AIM-120D	7400	800	105000	C47 B126	20C	FRAG-HE
AIM-120D-5	9705	800	200000	C47 B126	20C	FRAG-HE